

Embedded Computing Client (ECC)- Linux

The most advanced range of customized Thin Clients for all Verticals. ECC-LXC is a highly efficient and powerful thin client for both local computing, virtual desktop environments, Web Enables & ERP. It has a Linux style desktop with Linux flavours.



Breeze ECC LXC



MAIN FEATURES

- Latest Kernel support
- Office suite
- Browser
- Firefox
- *chrome/*Opera
- Touch Screen Support
- On Screen Keyboard for Touch Screen
- Dual Monitor Support
- Music Player
- Video Player
- File Browser
- Scanner Support
- PDF Viewer
- Email Client
- Image Viewer
- Ssh, Telnet , Rlogin, Rsh support
- Remote Desktop Client
- VNC Support
- CUPS Printing support
- Built in menu to configure thin client
- Backup Tool
- Skype (optional)
- Spotify (optional)
- System Applications
- Gnome Fonts support
- Gnome Screen shots

BREEZE INNOVATIONS Pvt. LTD.

MAIN SPECIFICATION

SYSTEM	
Chassis	Black chassis having front power button & Process Indicator (LED)
Processor	Intel Celeron J1800/J1900 "Bay Trail" 2.41GHz Dual Core/2.0 GHz Quad Core SOC
Operating System	Embedded Linux /Ubuntu (Ver as per requirement)
Protocol Support	XRDP, XDM, X11
MEMORY	
RAM (DDR3)	1x SO-DIMM socket Supports max. 8 GB DDR3)
Storage (Flash SSD)	16GB or above & secondary Storage (optional)
DISPLAY	
Port	HDMI 1x & VGA x 1,HDMI output supports DVI-D with optional adapter
Graphics	Supports Full HD 1080P Blu-ray / HD-DVD Playback
Color Depth	32 bits
Dual Display	Supported
NETWORK	
LAN	x1 (10/100/1000 Base-T Fast Ethernet, RJ-45)
WLAN	Optional
I/O PERIPHERAL INTERFACE	
USB 2.0	x 6 (front 2x, rear 4x)
USB 3.0	1x
Serial Port	2x - optional
Parallel port	1x -Optional
Other	LVDS
AUDIO	
Ports	Front & Back: Speaker-out x 1 , Mic-in x 1, (1/8-inch mini jack)
DIMENSION	
Device	212mm x 62.8mm x 210.6mm
Packaging	110mm x 312mm x 307mm
Net Weight	1.6 kg nett
POWER	
Adapter	100-240V AC, 50Hz, 19V/3.42A DC
Power Consumption	Maximum Rating 65W (Actual consumption less than 35W)
Certification & Compliance	
BIS(Bureau of India Standards)	Reg. No. R-67000159
RoHS	RoHS Compliant
ENVIRONMENT	
Cooling	Fan-less Convection
Operation Temperature	0°C to 40°C
Relative Humidity	30% to 90% non-condensing

The information contained herein is subject to change without notice. Breeze shall not be liable for technical or editorial errors or omissions contained herein.

