

MAIN SPECIFICATION

SYSTEM

Chassis	Black chassis having front power button & Process Indicator (LED)
Processor	Intel CPU 2.0 GHz Quad Core Fan less
Operating System	Embedded Linux (as per requirement)
Emulation Support	X Windows, VT100, VT200, VT220 & VT320

DISPLAY

Port	HDMI 1x & SVGA x 1
Monitor	17" or higher TFT color monitor (resolution 1280 x 1024 @60 Hz)

MEMORY

RAM (DDR3)	1x SO-DIMM socket Supports max. 8 GB DDR3)
Flash Memory	8GB MLC (16GB MLC flash with 8GB usable & 8GB for Over Provisioning) in Primary
Redundant Flash	8GB MLC (16GB MLC flash with 8GB usable & 8GB for Over Provisioning) in Secondary

NETWORK

LAN	x1 (10/100/1000 Base-T Fast Ethernet, RJ-45)
WLAN	Optional

I/O PERIPHERAL INTERFACE

USB 2.0	x 6 (front 2x, rear 4x)
USB 3.0	1x
Serial Port	3x or above
Parallel port	1x
Other	LVDS

AUDIO

Ports	Front & Back: Speaker-out x 1 , Mic-in x 1, (1/8-inch mini jack)
-------	--

DIMENSION

Device	212mm x 62.8mm x 210.6mm
Packaging	110mm x 312mm x 307mm
Net Weight	1.6 kg nett

POWER

Adapter	100-240V AC, 50Hz, 19V/3.42A DC
Power Consumption	Maximum Rating 65W (Actual consumption less than 35W)

Certification & Compliance

BIS(Bureau of India Standards)	Reg. No. R-67000159
RoHS	RoHS Compliant

ENVIRONMENT

Cooling	Fan-less Convection
Operation Temperature	0°C to 40°C
Relative Humidity	30% to 90% non-condensing

The information contained herein is subject to change without notice. Breeze shall not be liable for technical or editorial errors or omissions contained herein.

