

MAIN SPECIFICATION

SYSTEM

Chassis Black chassis having front power button & Process Indicator (LED)

Processor Intel CPU 2.0 GHz Quad Core Fan less

Operating System Embedded Linux (as per requirement)

Emulation Support X in s

DISPLAY

Port HDMI 1x & VGA x 1

Monitor 15.6" or higher TFT color monitor (resolution 800 x 600)

MEMORY

RAM (DDR3) 1x SO-DIMM socket Supports max. 8 GB DDR3)

Flash Memory 8GB MLC (16GB MLC flash with 8GB usable & 8GB for Over Provisioning) in Primary

Redundant Flash 8GB MLC (16GB MLC flash with 8GB usable & 8GB for Over Provisioning) in Secondary

NETWORK

LAN x1 (10/100/1000 Base-T Fast Ethernet, RJ-45)

WLAN Optional

I/O PERIPHERAL INTERFACE

USB 2.0 x 6 (front 2x, rear 4x)

USB 3.0 1x

Serial Port 2x - optional

Parallel port 1x -Optional

Other LVDS

AUDIO

Ports Front & Back: Speaker-out x 1 , Mic-in x 1, (1/8-inch mini jack)

DIMENSION

Device 212mm x 62.8mm x 210.6mm

Packaging 110mm x 312mm x 307mm

Net Weight 1.6 kg nett

POWER

Adapter 100-240V AC, 50Hz, 19V/3.42A DC

Power Consumption Maximum Rating 65W (Actual consumption less than 35W)

Certification & Compliance

BIS(Bureau of India Standards) **Reg. No. R-67000159**

RoHS RoHS Compliant

ENVIRONMENT

Cooling Fan-less Convection

Operation Temperature 0°C to 40°C

Relative Humidity 30% to 90% non-condensing

The information contained herein is subject to change without notice. Breeze shall not be liable for technical or editorial errors or omissions contained herein.

