

Embedded Computing Client (ECC)- WINDOWS

The most advance range of customized Thin Clients for all Verticals. ECC-W200 is a highly efficient and powerful thin client for both local computing, virtual desktop environments, web enabled and ERP. It has a Windows style desktop.



Breeze ECC W200



MAIN FEATURES

- Cost-effective
- High reliability, no moving parts
- Low power consumption
- Low CO2 emission
- High ROI
- Enhanced Security
- Highly Customizable in terms of software as well as hardware
- Legacy ports support
- Dual Flash (optional)
- All windows WES7/WIN 10 IOT features supported
- Internet Explorer 11.0
- Support for EWF & UWF Manager
- Multi-user / Single user login support.
- Time synchronization option from central server
- DHCP, DNS & WINS Support.
- Support for Telnet
- Mozilla Firefox (Optional)
- Chrome Browser (Optional)
- PDF reader, Open office, Flash Player, JVM,
- Calculator
- Latest Windows Update

BREEZE INNOVATIONS Pvt. LTD.

MAIN SPECIFICATION

SYSTEM	
Chassis	Black chassis having front power button & Process Indicator (LED)
Processor	Intel 2.0 GHz or above Dual Core/ Quad Core SOC
Operating System	Win 10 IOT
Protocol Support	Microsoft RDP, Citrix & VMware
MEMORY	
RAM (DDR3/DDR4)	1x SO-DIMM socket Supports max. 8 GB
Storage (Flash SSD)	16GB to 480GB & secondary Storage (optional)
DISPLAY	
Port	HDMI 1x & VGA x 1, HDMI output supports DVI-D with optional adapter
Graphics	Supports DirectX® 11 Supports Full HD 1080P Blu-ray / HD-DVD Playback
Color Depth	32 bits
Dual Display	Supported
NETWORK	
LAN	x1 (10/100/1000 Base-T Fast Ethernet, RJ-45)
WLAN	Optional
I/O PERIPHERAL INTERFACE	
USB 2.0	x 6 (front 2x, rear 4x) or x 4 (front 2x, rear 2x)
USB 3.0	1x or 4x
Serial Port	2x - optional
Parallel port	1x -Optional
Other	Kensington Lock- Optional
AUDIO	
Ports	Front & Back: Speaker-out x 1 , Mic-in x 1, (1/8-inch mini jack)
DIMENSION	
Device	212mm x 62.8mm x 210.6mm
Packaging	110mm x 312mm x 307mm
Net Weight	1.6 kg nett
POWER	
Adapter	100-240V AC, 50Hz, 19V/3.42A DC
Power Consumption	Maximum Rating 65W (Actual consumption less than 35W)
Certification & Compliance	
BIS(Bureau of India Standards)	Reg. No. R-67000159
RoHS	RoHS Compliant
ENVIRONMENT	
Cooling	Fan-less Convection
Operation Temperature	0°C to 40°C
Relative Humidity	30% to 90% non-condensing

The information contained herein is subject to change without notice. Breeze shall not be liable for technical or editorial errors or omissions contained herein.

